
PDS (Product data sheet) of Kanpromax 15W 40 CH-4

Description:

Kanpromax 15W 40 CH-4 is a premium quality heavy duty lubricant designed specifically to meet wide range of passenger car engines and light industrial vehicles. It can be used in city, road, and highway, during all seasons. It has perfect lubricating properties and viscosity stability combined with deposit and wear control

Applications:

Kanpromax 15W 40 CH-4 engine Oil is recommended for passenger cars, light trucks SUV's and vans, gasoline powered equipment and four strokes' motorcycles engines under the most severe and varied operating conditions.

Performance Benefits:

Improved control of volatility and oil consumption.
Protects against soot, varnish, and sludge formation.
Highly effective control over wear, corrosion and rust
Exceptional resistance to oxidation and foaming.
Excellent dispersive and detergent properties which ensure a clean engine.
Improved protection during start-up by maintaining protective oil films.
Increase engine efficiency.

Technical Specifications:

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	L2.5
Density @ 15 °C, Kg/L	D-1298	0.8725
Viscosity @ 100 °C, cst	D-445	14.6
Viscosity @ 40 °C, cst	D-445	110.6
Viscosity index	D-2270	136
Flash Point, °C (COC)	D-92	236
Pour Point, °C	D-97	-32
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	8.5
CCS at -20°C (mPa.s)	D-5293	6800

Health and Safety:

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.kanpromax.com